

Elegant and compact design



# Record Vision Touch Speed Gate

Sophisticated detection methods for maximum security

A reliable and sophisticated entrance control solution which creates a fluid barrier, enabling a fast and steady flow of people without compromising security.

## Applications

Especially suitable for transport hubs, office buildings, airports, stadiums or any premises that requires visitors to be authorised.

## Key benefits

- » User-friendly and ergonomic design for ease of use
- » Reliable and robust construction for a long life-span with minimal service required
- » Easy access for the elderly or those who struggle with mobility
- » Compatibility with existing security systems means a hassle free installation
- » Modern appearance to complement any architectural design
- » Automates checking visitors credentials removing the burden from staff

## Barrier wing height



960 mm



1200 mm



1800 mm

## Customisable security

Available in various finishes and dimensions, such as 1.2m or 1.8m height, to suit individual needs and maintain the aesthetics of the surroundings.

## Emergency & power cut

In case of an emergency alarm gate leaves can be set to become unlocked and move freely, or remain open in a specified direction for the alarm duration.

## Access control integration

Vision Touch can be controlled by any kind of access control system through dry contact or COM parts. Optional cutouts are available for reader holders or stands as well as standard or custom designed posts for access controller integration.

Key features

- » Illuminated pictograms for intuitive user guidance
- » Quick and easy integration of access control system technologies and biometrics
- » Advanced sensor technology for increased safety
- » Energy efficient and sustainable performance
- » Accessible for wheelchair users and people with push chairs
- » Intrusion alarm sounds in case of unauthorised entry
- » Various wing heights available to suit your needs

LED indicators

|       |                   |
|-------|-------------------|
| Blue  | Waiting mode      |
| Green | Passage confirmed |
| Red   | No passage        |

Settings

|                                   |                          |
|-----------------------------------|--------------------------|
| Operation mode for each direction | Controlled, free, locked |
| Audible notifications             | On/off                   |
| Release time                      | 5, 10, 15, 25 secs       |
| Emergency connection              | On/off                   |

Technical specifications

|                          |  |
|--------------------------|--|
| Cabinet material         | Stainless steel brushed AISI 304<br>Stainless steel brushed AISI 316<br>Mild steel powder coated (RAL) |
| Wing material            | 10mm tempered glass  |
| Cabinet weight           | 115 kg/ 155 kg   |
| IP rating                | IP 44  |
| Cabinet length           | 1319 mm  |
| Cabinet height           | 1000 mm  |
| Cabinet width            | 132 mm (without rotor)   |
| Wing height              | 960 - 1800 mm  |
| Passage width            | 500 - 1000 mm  |
| Capacity                 | 40/min   |
| Internal RFID Dimensions | L = 140 mm x W= 69 mm x D = 40 mm  |
| Available inputs         | Card reader for entry and exit, fire alarm, external control panel                                     |
| Power supply             | 110/240 VAC, 50/60 Hz  |
| Energy consumption       | 75W/50W  |
| MCBF                     | 10,000,000<br>(with recommended maintenance)   |
| MTTR                     | < 30 min.  |
| Operating temperature    | +0°C to +70°C  |



Dimensions

